



# ACE DIESEL

LAMBE SAFAR KA  
BHAROSEMAND SAATHI

Ab behtar performance aur  
profitability ke saath

**BS6 P2** >>>  
**Phase 2**

### ENHANCED SAFETY



BIGGER HEADLAMPS

### BETTER FEATURES



NEW UPGRADED CABIN

### BETTER DRIVEABILITY



REDUCED STEERING  
EFFORT

### ENHANCED COMFORT



SEAT WITH HEADREST

### HIGH POWER AND PICKUP



POWER MODE SWITCH

SPECIFICATIONS	
Engine Description:	4 Stroke, Naturally Aspirated, Direct Injection Common Rail Diesel engine
Engine Capacity	702 cc
Max Engine Output	POWER Mode - 14.7 kW @ 3 600 r/min CITY Mode -13.2 kW @ 3 600 r/min
Max. Torque	POWER Mode - 45 Nm @ 1 800 - 2 200 r/min CITY Mode - 39 Nm @ 1 800 - 2 200 r/min
No. of Gears	4-Forward 1-Reverse
Clutch	Single plate dry friction diaphragm type
Steering	Mechanical, variable ratio
Front Suspension	Parabolic leaf spring
Leaf Width	60 mm (Front) , 70 mm (Rear)
Rear Suspension	Semi - Elliptical leaf spring
Shock Absorber	Hydraulic double acting telescopic type
Tyres	145R12 LT 8PR Radial Tubeless Tyres
Max. Gradeability at rated GVW	27 % (Power Mode)
Max. Speed	65 kmph (Power Mode)
Gross Vehicle Weight	1 675 kg
Payload	750 kg
Fuel Tank Capacity	30 L
Urea Tank Capacity	10.5 L
Dimensions	
Length	3 800 mm
Width	1 500 mm
Height	1 845 mm
Wheelbase	2 100 mm
Front Track	1 300 mm
Rear Track	1 320 mm
Min TCR	4 300 mm
Ground Clearance	160 mm
Cargo Box Dimensions	2200 mm x 1490 mm x 300 mm
Seating	D+1



**ENHANCED  
MILEAGE**



**MORE  
POWER**



**MORE  
TORQUE**



**LOW  
MAINTENANCE**

**EXTRA FEATURES FOR EXTRA COMFORT**



The illustrations and photographs may show accessories and items of optional equipment which are not part of the standard specifications. Due to printing processes, colours may vary slightly from those shown. All listed specifications are current and subject to change or upgrade without prior notice, in accordance with the company's policy of continuous improvement. Terms & conditions apply.