

ACE HI⁺

A Reliable Partner for Longer Journeys



**1 100 kg
PAYLOAD**

**AB UTHAYE AUR
BHI ZYADA**



**2 520 mm (8'3")
Long Load Body**



**13"
Bigger Tyres**



**ECO
Switch**



**With
Turbo Charger**





ENHANCED
MILEAGE



MORE
POWER



MORE
TORQUE



LOW
MAINTENANCE

EXTRA FEATURES FOR EXTRA COMFORT

*T&C Apply

The illustrations and photographs may show accessories and items of optional equipment which are not part of the standard specifications. Due to printing processes, colours may vary slightly from those shown. All listed specifications are current and subject to change or upgrade without prior notice, in accordance with the company's policy of continuous improvement. Terms & conditions apply.

Parameters	Ace HT+
Engine Description	Four Stroke, Compression Ignition, Direct Injection Common Rail, Turbocharged Intercooled
Engine Capacity	798 CC
Max Engine Output / Power	26 kW (35 hp) @ 3 750 rpm
Max Torque	85 Nm @ 1 750 - 2 750 rpm
Gearbox	5 Forward, 1 Reverse (GBS 65-5/5.07)
Clutch	Single plate dry friction diaphragm type
Steering	Mechanical
Type of Fuel	Diesel
Fuel Tank Capacity	30L
DEF Tank Capacity	10.5L
Max Speed	80 km/h
Max. Gradeability at rated GVW	32%
Brakes	Front - Disc brakes; Rear - Drum Brakes
Suspension	Front - Rigid Axle with Parabolic Leaf Spring Rear - Live Axle with semi-elliptical Leaf Spring
Tyres	155 R13
Dimensions	
Length (mm)	4 075
Width (mm)	1 500
Height (mm)	1 858
Wheelbase (mm)	2 250
Ground Clearance (mm)	160
Cargo Box Dimensions (External) (mm)	2520 x 1490 x 300 (8'3" X 4'10")
Min TCR (Turning Circle Radius) (mm)	4 625
Weight	
Max GVW (kg)	2 120
Kerb Weight (kg)	1 020
Payload (kg)	1 100
Seats	D+1
Warranty	3 Year / 1 00 000 km* (whichever is earlier)