

# INTRA V20 GOLD PICKUP

SUCCESS KA MANTRA

BI-FUEL  CNG +  PETROL



800\*+ km  
Long Range



Fuel Tank Capacity  
CNG 110 L + Petrol 35/5 L



Long Load Body  
2 690 mm (8'9")



Electric Power  
Assisted Steering





Parameters	Intra V20 Gold
<b>Engine Description</b>	1.2L NGNA CNG, 3 Cylinder engine
<b>Engine Capacity</b>	1 199 CC
<b>Max Engine Output / Power</b>	Petrol : 43 kW (58.4 hp) @ 4 000 rpm CNG : 39 kW (53 hp) @ 4 000 rpm
<b>Max Torque</b>	Petrol : 106 Nm @ 1 800 - 2 200 rpm CNG : 95 Nm @ 1 800 - 2 200 rpm
<b>Gearbox</b>	GBS 65 Synchronesh 5F + 1R
<b>Clutch</b>	Single plate dry friction diaphragm type
<b>Steering</b>	Electric Assisted Power Steering
<b>Type of Fuel</b>	CNG + Petrol
<b>Fuel Tank Capacity</b>	Intra V20 GOLD - CNG : 110 L (45+35+30)   Petrol : 35L / 5L Intra V20 - CNG : 80 L (45+35)   Petrol : 35L / 5L
<b>DEF Tank Capacity</b>	NA
<b>Max Speed (km/h)</b>	80
<b>Max. Gradeability at rated GVW</b>	25 % (CNG Mode), 27 % (Petrol Mode)
<b>Brakes</b>	Front - Disc brakes; Rear - Drum Brakes
<b>Suspension</b>	Front - Semi elliptical leaf springs - 4 leaves Rear - Semi elliptical leaf springs - 6 leaves
<b>Tyres</b>	165 R14

Dimensions	
<b>Length (mm)</b>	4 460
<b>Width (mm)</b>	1 692
<b>Height (mm)</b>	1 921
<b>Wheelbase (mm)</b>	2 450
<b>Ground Clearance (mm)</b>	175
<b>Cargo Box Dimensions (External) (mm)</b>	2 690 X 1 620 X 300 (8'9" X 5'3")
<b>Min TCR (Turning Circle Radius) (mm)</b>	5 250

Weight	
<b>Max GVW (kg)</b>	Intra V20 Gold : 2 505   Intra V20 : 2 275
<b>Kerb Weight (kg)</b>	Intra V20 Gold : 1 305   Intra V20 : 1 275
<b>Payload (kg)</b>	Intra V20 Gold : 1 200   Intra V20 : 1 000
<b>Seats</b>	D+1
<b>Warranty</b>	3 Year or 1 00 000 km* (Whichever is earlier)

**Enhanced Payload of 1 200 kg**

**Enhanced Pickup**

**Comfortable to drive**

**Fleet Edge**

**EXTRA FEATURES FOR EXTRA COMFORT**

\*T&C apply  
The illustrations and photographs may show accessories and items of optional equipment which are not part of the standard specifications. Due to printing processes, colours may vary slightly from those shown. All listed specifications are current and subject to change or upgrade without prior notice, in accordance with the company's policy of continuous improvement. Terms & conditions apply.