

INTRA V30 GOLD PICKUP

SUCCESS KA MANTRA



**1 500 kg
PAYLOAD**

**AB UTHAYE AUR
BHI ZYADA**



**Strong
Chassis**



**160 Nm
High Pickup**



**52 kW (70 hp)
High Engine Power**



**Electric Power
Assisted Steering**





FOOD GRAIN
SACKS



CEMENT
SACKS



FRUITS AND
VEGETABLES -
CRATES



FARM LOAD



CONSTRUCTION
MATERIAL



COLD DRINK
CRATES



WATER
BOTTLES



Enhanced Payload
of 1 500 kg



Enhanced
Pickup



Electric Power
Assisted Steering



FLEET EDGE



Enhanced Payload with Better Stability

Parameters	Intra V30 Gold
Engine Description	TATA 4 cylinder 1.5L DI engine, 1497 cc
Engine Capacity	1 497 CC
Max Engine Output / Power	52 kW (70 hp) @ 4 000 rpm
Max Torque	160 Nm @ 1 800 – 3 000 rpm
Gearbox	GBS 65 Synchromesh 5F + 1R
Clutch	Single plate dry friction diaphragm type
Steering	Electric Assisted Power Steering
Type of Fuel	Diesel
Fuel Tank Capacity	35 L
DEF Tank Capacity	NA
Max Speed (km/h)	80
Max. Gradeability at rated GVW	38%
Brakes	Front - Disc brakes; Rear - Drum Brakes
Suspension	Front - Semi elliptical leaf springs - 5 leaves Rear - Semi elliptical leaf springs - 8 leaves
Tyres	185 R14 LT 8PR
Dimensions	
Length (mm)	4 460
Width (mm)	1 692
Height (mm)	1 945
Wheelbase (mm)	2 450
Ground Clearance (mm)	175
Cargo Box Dimensions (External) (mm)	2 690 X 1 620 X 400 (8'9" X 5'3")
Min TCR (Turning Circle Radius) (mm)	5 250
Weight	
Max GVW (kg)	2 760 (CX & LX) / 2 775 (VX)
Kerb Weight (kg)	1 260 (CX & LX) / 1 275 (VX)
Payload (kg)	1 500
Seats	D+1
Warranty	3 Year or 1 00 000 km* (Whichever is earlier)

T* & C apply

The illustrations and photographs may show accessories and items of optional equipment which are not part of the standard specifications. Due to printing processes, colours may vary slightly from those shown. All listed specifications are current and subject to change or upgrade without prior notice, in accordance with the company's policy of continuous improvement. Terms & conditions apply.