

# INTRAV50 GOLD PICKUP

## SUCCESS KA MANTRA



**1 700 kg  
PAYLOAD**

**AB UTHAYE AUR  
BHI ZYADA**



**Strong  
Chassis**



**220 Nm  
High Pickup**



**60 kW (80 hp)  
High Engine Power**



**Long Load Body  
2 960 mm (9'8")**





FOOD GRAIN  
SACKS



CEMENT  
SACKS



FRUITS AND  
VEGETABLES -  
CRATES



FARM LOAD



CONSTRUCTION  
MATERIAL



MILK CRATES



LPG  
CYLINDERS



1 700 kg PAYLOAD



5.18 M<sup>2</sup> LARGE  
LOAD BODY



10 LEAF SPRING  
SUSPENSION (REAR)



FLEET EDGE



Enhanced Payload with Better Stability

Parameters	Intra V50 Gold
Engine Description	1.5L 4-cylinder Common Rail Turbo Intercooled Diesel Engine
Engine Capacity	1 497 CC
Max Engine Output / Power	60 kW (80 hp) @ 4 000 rpm
Max Torque	220 Nm @ 1 750 - 2 500 rpm
Gearbox	G5220 Synchronesh 5F + 1R
Clutch	Single plate dry friction diaphragm type
Steering	Hydraulic Assisted Power Steering
Type of Fuel	Diesel
Fuel Tank Capacity	35 L
DEF Tank Capacity	NA
Max Speed	80
Max. Gradeability at rated GVW	34%
Brakes	Front - Disc brakes; Rear - Drum Brakes
Suspension	Front - Parabolic leaf spring - 2 leaves Rear - Semi-elliptical leaf springs - 10 leaves
Tyres	215/75 R15
Dimensions	
Length (mm)	4 734
Width (mm)	1 750
Height (mm)	2 014
Wheelbase (mm)	2 600
Ground Clearance (mm)	193
Cargo Box Dimensions (External) (mm)	2 960 X 1 750 X 400 (9'8" X 5'8")
Min TCR (Turning Circle Radius) (mm)	6 050
Weight	
Max GVW (kg)	3 160 (CX, LX)   3 210 (VX)
Kerb Weight (kg)	1 460 (LX)   1 455 (CX)   1 510 (VX)
Payload (kg)	1 700
Seats	D+1
Warranty	3 Year or 1 00 000 km* (Whichever is earlier)

\*T&C apply

The illustrations and photographs may show accessories and items of optional equipment which are not part of the standard specifications. Due to printing processes, colours may vary slightly from those shown. All listed specifications are current and subject to change or upgrade without prior notice, in accordance with the company's policy of continuous improvement. Terms & conditions apply.