

**TATA MOTORS**  
COMMERCIAL VEHICLES

Better  
Always



# YODHA

4X4

NO ROAD IS IMPOSSIBLE



1 210 kg  
Payload



74.8 kW (100 hp)  
High Engine Power



250 Nm  
High Pickup



35% High  
Climbing Ability



Parameters	Yodha 4X4 Single Cabin	Yodha 4X4 Crew Cab
<b>Engine Description</b>	TATA 2.2 L VARICOR Intercooled Turbocharged BS6 DI engine	TATA 2.2 L VARICOR Intercooled Turbocharged BS6 DI engine
<b>Engine Capacity</b>	2 179 CC	2 179 CC
<b>Max Engine Output / Power</b>	74.8 kW (100 hp) @ 3 750 rpm	74.8 kW (100 hp) @ 3 750 rpm
<b>Max Torque</b>	250 Nm @ 1 000 - 2 500 rpm	250 Nm @ 1 000 - 2 500 rpm
<b>Gearbox</b>	G76 - 5/4.49 Synchromesh 5F + 1R	G76 - 5/4.49 Synchromesh 5F + 1R
<b>Clutch</b>	Single Plate dry Friction type	Single Plate dry Friction type
<b>Steering</b>	Hydraulic Assisted Power Steering	Hydraulic Assisted Power Steering
<b>Type of Fuel</b>	DIESEL	DIESEL
<b>Fuel Tank Capacity</b>	52 L	52 L
<b>DEF Tank Capacity</b>	NA	NA
<b>Max. Gradeability at rated GVW</b>	35%	35%
<b>Brakes</b>	Front : Hydraulic, Twin Pot Disc Brake ; Rear : Drum Brakes	Front : Hydraulic, Twin Pot Disc Brake ; Rear : Drum Brakes
<b>Suspension</b>	Front - Rigid Suspension with Semi-elliptical Leaf Spring , Rear - Innovative Two Stage Semi-elliptical Leaf Springs	Front - Rigid Suspension Leaf Spring and Shock Absorber Rear - Semi-elliptical type with Hydraulic Double Acting Telescopic Shock Absorber
<b>Tyres</b>	215/75 R15	215/75 R15
<b>Dimensions</b>		
<b>Length (mm)</b>	5 025	5 350
<b>Width (mm)</b>	1 860	1 860
<b>Height (mm)</b>	1 810	1 810
<b>Wheelbase (mm)</b>	2 975	3 300
<b>Ground Clearance (mm)</b>	190	190
<b>Cargo Box Dimensions (External ) (mm)</b>	2 317 X 1 790 X 325 (7'7" X 5'10")	1 874 X 1 843 X 415 (6'1" X 6'0")
<b>Min TCR (Turning Circle Radius) (mm)</b>	6 750	6 250
<b>Weight</b>		
<b>Max GVW (kg)</b>	2 990	2 990
<b>Kerb Weight (kg)</b>	1 780	1 930
<b>Payload (kg)</b>	1 210	1 060
<b>Seats</b>	D+1	D+4
<b>Warranty</b>	3 Year / 3 Lakh km* (Whichever is earlier)	3 Year / 3 Lakh km* (Whichever is earlier)

\*T&C Apply

The illustrations and photographs may show accessories and items of optional equipment which are not part of the standard specifications. Due to printing processes, colours may vary slightly from those shown. All listed specifications are current and subject to change or upgrade without prior notice, in accordance with the company's policy of continuous improvement. Terms & conditions apply.