

Connecting Aspirations






DURABLE PICKUP THAT IS HIGH ON PERFORMANCE

AND EASY ON YOUR POCKET

SUPERIOR COMFORT



RELIABILITY (C)

Dedicated service support for Yodha customers provides total reliability and minimizes your downtime.



Powerful engine that delivers 74.8 kW (100 hp) power & 250 Nm torque to ensure faster deliveries.

LOW TO MAINTENANCE

Longer engine oil change interval (20 000 km) and stronger aggregates to keep maintenance cost low & profits high.







POWER AND PICKUP

A powerful engine that produces 74.8 kW (100 hp) power & 250 Nm torque to make you an unstoppable force on the road.

UNMATCHED STABILITY

Anti-roll bar on the front side to give improved stability and a bigger wheelbase (3.30 m) to provide superior driving comfort.

LOW MAINTENANCE

Enhances savings through a longer engine oil change interval (20 000 km) and aggregates that are lubricated for life.




Connecting Aspirations



YODHA **CREW CAB EX**

GET READY TO CONQUER ANY TERRAIN WITH A POWERFUL PICKUP BUILT FOR SUPERIOR GRADABILITY AND OFF-ROADING CAPABILITIES.


SUPERIOR DRIVABILITY THROUGH TOUGH **TERRAINS**



drivability even on unpaved roads.

LOW MAINTENANCE
The Yorks For C The Yodha Ex Crew Cab enhances savings through a longer engine oil change interval of 20 000 km and Lubricated For Life aggregates.

FASTER TURNAROUND TIME



LUXURY & COMFORT

Dedicated service support for Yodha customers provides total reliability and minimizes your downtime.







Connecting Aspirations



READY TO ENHANCE PERFORMANCE IN EVERY APPLICATION, ACROSS EVERY TERRAIN

MILK TRANSPORT



CONSTRUCTION & MINING





Models	Yodha crew cab 4x2	Yodha Crew Cab IFS	Yodha crew cab 4x4
Engine type	TATA 2.2L VARICOR Intercooled Turbocharged BS6 DI engine		
Max engine output	74.8 kW (100 hp) @ 3 750 r/min		
Max engine Torque	250 Nm @ 1 000 -2 500 r/min		
Clutch	Single Plate dry Friction type 260 mm Dia		
Gearbox	G76 - 5/4.49 Synchromesh 5F + 1R		
Steering	Power Steering		
Front suspension	Rigid Suspension with leaf spring & Shock absorber	Double wishbone type with independent coil Spring	Rigid Suspension with leaf spring & Shock absorber
Rear suspension	Semi-elliptical type with Hydraulic Double Acting Telescopic Shock Absorber	Parabolic Leaf Springs	Semi-elliptical type with Hydraulic Double Acting Telescopic Shock Absorber
Anti Roll Bar	Front		
Front brakes	Hydraulic, twin pot Disc Brake		
Rear brakes	Drum Brakes		
Tyre	215/75 R 16 Radial tubeless		215/75 R 15 LT
Rim size	16"		15"
Load body	1 880 mm (6.2 ft.) x 1 850 mm (6 ft.)		
Load body floor	Flatbed Load Body		
Turning Circle Radius	6 250 mm		
Air conditioning (HVAC)	Optional	Optional	NA
		Overall Vehicle Dimensions	
Wheel Base (mm)	3 300		
Width (mm)	1 860		
Length (mm)	5 350		
Height (mm)	1810		
Ground Clearance (mm)	210 mm		190 mm
		Weights (kg)	
GVW	2 990		
Kerb weight	1 850	1 890	1 930
Payload	1 140	1 100	1 060
		Performance	
Gradability	40 %		30 %
Seating capacity		D+4	
		Warranty Terms	
Engine Oil change interval	20 000 km	20 000 km (10 000 km for Hilly & off road conditions)	20 000 km (10 000 km for Hilly & off road conditions)
Warranty (On Driveline)	3 Years/3 Lakh km	3 Years/3 Lakh km	3 Years/3 Lakh km

Get regular updates on



//o /tatamotorssmalltrucks

